

POLYFLOR CAMARO WOOD PUR

- Camaro - collection of versatile vinyl floor products
- Wood effect floorcovering designs
- Coordinating grouting, marquetry and feature strips are readily available to blend, shape or accentuate design ideas

SPECIFICATION



2.0mm



0.3mm



36 @ 101 x 914mm = 3.34m²
 24 @ 152 x 914mm = 3.34m²
 18 @ 152 x 1219mm = 3.34m²
 14 @ 203 x 1219mm = 3.46m²



3600g/m²



GENERAL PERFORMANCE

EN 649
 EN ISO 10582



REACTION TO FIRE
 EN 13501-1 Class Bfl-S1



SLIP RESISTANCE
 EN 13983 Class DS*
 DIN 51130 R10
 AS/NZS 4586 R10
 For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges



LIGHT FASTNESS
 ISO 105-B02 Method 3 ≥6



ABRASION RESISTANCE
 EN 649 Group T
 EN ISO 10582 Type 1



ELECTRICAL BEHAVIOUR (body voltage)
 EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



INDENTATION - RESIDUAL
 EN 433 ≤ 0.05mm
 EN ISO 24343-1 ≤ 0.05mm



DIMENSIONAL STABILITY
 EN 434 ≤ 0.1% max.
 EN ISO 23999 ≤ 0.1% max.



CASTOR CHAIR (continuous use)
 EN 425 / ISO 4918 Suitable



THERMAL CONDUCTIVITY
 Suitable for underfloor heating Max. 27°C



VOC EMISSIONS
 Indoor Air Comfort GOLD - Eurofins certified product
 AgBB - Very low emissions
 FloorScore - Certified product



ENVIRONMENTALLY PREFERABLE FLOORING
 Polyflor Camaro PUR achieves a BRE Global Environmental A+ rating (Certificate No: ENP 429). Polyflor Camaro PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



APPLICATIONS
 Polyflor Camaro PUR is suitable for use in any domestic situation and moderate commercial areas such as offices, hotels and boutiques.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
 * For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Halstead
 FLOORING



2011




CAMARO™
 FLOORING COLLECTION

WOOD



PERFORMANCE AND PROPERTIES

A+BRE
 ENP 429 ENVIRONMENTAL RATING
 Refer to BRE Global ratings on www.greenbooklive.com



POLYFLOR™
 COVERING THE WORLD